

**SAFETY DATA SHEET***Ardell Hair Fiber Building Fiber***SECTION 1. IDENTIFICATION***PRODUCT DESCRIPTION*

Ardell Hair Fiber Building Fiber

ITEM NUMBER

See Section 16

PRODUCT TYPE

Finished Good

RECOMMENDED USE

Personal Care Product

USES ADVISED AGAINST

All other uses

*MANUFACTURER*American International Industries
2220 Gaspar Ave
Los Angeles, CA 90040
Phone: (323) 728-2999*EMERGENCY PHONE*

CHEM-TEL: 1-(800)-255-3924

SECTION 2. HAZARD IDENTIFICATION

<i>HAZARD CLASS</i>	<i>CATEGORY</i>	<i>PICTOGRAM</i>
Not Classified	Not Classified	None
Signal word	None	
Hazard Statement	Non Hazardous	
Hazard Codes	None	
Precautionary Statements	P102 Keep out of reach of Children	
Other Hazards	HMIS: Health: 0 Flammability: 0 Physical hazard: 0	
Hazard Symbol	None	
Risk Phrases	None	
Safety Phrases	None	

**SAFETY DATA SHEET***Ardell Hair Fiber Building Fiber***SECTION 3. COMPOSITION**

This product does not contain hazardous chemicals according to the OSHA Hazardous Communication Standard 29 CFR §1910.1200.

COMPOSITION OF HAZARDOUS CHEMICALS

Chemical Name	INCI Name	CAS No.	% w/w
NONE	NONE	NONE	NONE

SECTION 4. FIRST AID MEASURES*GENERAL ADVISE*

Though this product is non hazardous for its indented use, in all cases, if symptoms persists contact a physician.

ROUTES OF ENTRY

EYE CONTACT	Rinse with plenty of water for at least 15 minutes. Remove contact lenses, if present, after the first 5 minutes, and then continue rinsing. May be mildly irritating in sensitive individuals. Abrasion may cause eye irritation.
SKIN CONTACT	Mild skin irritation may occur in sensitive individuals. Wash with soap and water. The abrasiveness of talc may cause skin irritation.
INHALATION	Inhalation of dusts may cause sneezing, coughing and nose irritaiton.
INGESTION	May cause mild irritation of gastrointestinal tract. Clean mouth with water and afterwards drink plenty of water. Do not induce vomiting. Contact a physician.

MOST IMPORTANT SYMPTOMS/EFFECTS ACUTE OR DELAYED

Non known

NOTES TO PHYSICIAN

Treat symptomatically

SECTION 5. FIRE-FIGHTING MEASURES*FLAMMABILITY*

Non flammable

FLASH POINT

>200°C

