



SAFETY DATA SHEET

Medi-Dan Classic Medicated Dandruff Treatment Shampoo

SECTION 1. IDENTIFICATION

PRODUCT DESCRIPTION

Medi-Dan Classic Medicated Dandruff Treatment Shampoo

ITEM NUMBER

11000, 11005

PRODUCT TYPE

Finished Good

RECOMMENDED USE

Personal Care Product

USES ADVISED AGAINST

All other uses

MANUFACTURER

American International Industries
2220 Gaspar Ave
Los Angeles, CA 90040
Phone: (323) 728-2999

EMERGENCY PHONE

CHEM-TEL: 1-(800)-255-3924

SECTION 2. HAZARD IDENTIFICATION

<i>HAZARD CLASS</i>	<i>CATEGORY</i>	<i>PICTOGRAM</i>
Not Classified	Not Classified	None
Signal word	None	
Hazard Statement	Non Hazardous	
Hazard Codes	None	
Precautionary Statements	P102 Keep out of reach of Children	
Other Hazards	HMIS: Health: 0 Flammability: 0 Physical hazard: 0	
Hazard Symbol	None	
Risk Phrases	None	
Safety Phrases	None	

**SAFETY DATA SHEET***Medi-Dan Classic Medicated Dandruff Treatment Shampoo***SECTION 3. COMPOSITION**

This product does not contain hazardous chemicals according to the OSHA Hazardous Communication Standard 29 CFR §1910.1200.

COMPOSITION OF HAZARDOUS CHEMICALS

Chemical Name	INCI Name	CAS No.	% w/w
Alcohol Denat	Alcohol Denat	64-17-5	2.50%
Isopropyl Alcohol	Isopropyl Alcohol	67-63-0	2.50%

SECTION 4. FIRST AID MEASURES*GENERAL ADVISE*

Though this product is non hazardous for its indented use, in all cases, if symptoms persists contact a physician.

ROUTES OF ENTRY

EYE CONTACT	Rinse with plenty of water for at least 15 minutes. Remove contact lenses, if present, after the first 5 minutes, and then continue rinsing. May be mildly irritating in sensitive individuals.
SKIN CONTACT	Mild skin irritation may occur in sensitive individuals. Wash with soap and water.
INHALATION	Not applicable
INGESTION	Clean mouth with water and afterwards drink plenty of water. May cause diarrhea. Do not induce vomiting. Contact a physician.

MOST IMPORTANT SYMPTOMS/EFFECTS ACUTE OR DELAYED

Non known

NOTES TO PHYSICIAN

Treat symptomatically

SECTION 5. FIRE-FIGHTING MEASURES*FLAMMABILITY*

Non flammable

FLASH POINT

>200°C

